


REMARKS

The specification and claims have been amended in accordance with U. S. practice. An Abstract has been added. The new claims generally correspond to the PCT prosecuted claims but which are drawn in accordance with U.S. patent practice. An additional independent claim 23 has also been added.

An Information Disclosure Statement is enclosed.

Submitted by,



(Reg. 27,841)

Schiff, Hardin LLP

CUSTOMER NO. 26574

Patent Department

6600 Sears Tower

233 South Wacker Drive

Chicago, Illinois 60606

Telephone: 312/258-5786

Attorneys for Applicant.

MARKED COPY

SPECIFICATION**TITLE**

**METHOD AND DEVICE FOR ADJUSTING TO A MINIMUM VALUE THE
TONER SUPPLY TO A DEVELOPING STATION OF AN
ELECTROGRAPHIC PRINTING OR COPYING UNIT**

5

BACKGROUND

Electrographic printing or copying devices (collectively called printing devices in the following) are known, for example, from EP-B1-0 683 954.

10 According to Fig. 1, such a printing device comprises a driven intermediate carrier ZT, for example, a photoconductor drum, on which are generated charge images of the images to be printed that are inked with toner, subsequently transfer printed onto a recording medium AT (for example paper) and fixed to this in a fixing station FX. For this, the printing device
15 comprises, for example, the following components grouped around the intermediate carrier ZT:

- a charge corotron L to charge the intermediate carrier ZT,
- an illumination device (character generator) DK,
- a developer station E,
- 20 - a transfer printing station UDS,
- a cleaning station R,
- an erasure corotron LSC,
- a discharge lamp EDL.

For example, the intermediate carrier ZT is charged to 500 V with the
25 charge corotron L and then discharged to, for example, approximately 70 V with the illumination device DK to generate the charge images of the images to be printed. The charge images are subsequently inked with toner in a typical manner in the developer station E. However, the transfer of toner onto the intermediate carrier ZT only occurs when a sufficient voltage exists
30 between the developer station E (for example a developer roller) and the discharged regions of the intermediate carrier ZT. If, for example, the developer roller exhibits a potential of 220 V and the charge images on the intermediate carrier ZT exhibit a potential of approximately 70 V, a field then

MARKED COPY

results that pulls the toner from the developer station E to the intermediate carrier ZT. The toner images are subsequently transferred to the recording medium AT in the transfer printing station UDS. Finally the intermediate carrier ZT is cleaned of residual toner in the cleaning station R. The
5 intermediate carrier ZT is prepared for a new printing event with the aid of the erasure corotron LSC and the discharge lamp EDL.

A developer made from carrier and toner (two-component developer) can be used in a known manner to develop the charge images on the intermediate carrier, whereby the fraction of toner is adjustable. In order to be
10 able to check the fraction of toner, it is known (for example from WO 99/36834 A) to apply what is known as a toner marking that can be inked with toner onto the intermediate carrier. The inked toner marking can be scanned with a sensor that emits a signal dependent on the area coverage at the measurement location. This measurement signal serves to adjust the fraction
15 of toner in the developer. The design of such a device and its operation can be learned from WO 99/36834 A, which is herewith included in the present disclosure. The toner supply into the developer station occurs in conveyer cycles that are implemented until the fraction of toner in the developer has reached the provided value.

20 A method for regulation of the toner supply in a developer station is known from US-A 5,410,388 A. For this, a toner marking is generated and scanned on the intermediate carrier. When the scan of the toner marking results in that the signals generated in the scan of the front region and the scan of the rear region of the toner marking are different, and the signal
25 associated with the front region is larger than the signal associated with the rear region, toner is conveyed into the developer station.

A method for control of the toner supply into a developer station is known from EP-A-0 546 953, in which the requirement for toner is determined and the scale of the supply of new toner per time unit is adjusted in the
30 developer station dependent on this requirement. Differently designed dosing rollers are used for this. The requirement for toner is established either via

MARKED COPY

counting of the image points of the images generated on the intermediate carrier or via measurement of the toner concentration in the developer station.

A method is known from US-A 5,387,965 with which the toner supply to a developer station is controlled such that unwanted changes of the developer
5 or of the intermediate carrier are taken into account. The toner concentration is thereby measured in the developer station by a sensor and compared with a predetermined reference value. Toner is conveyed into the developer station or not dependent on the comparison result.

A rule arrangement for a printing device is known from DE 38 07 121
10 A1, in which the developer station is controlled in order to achieve an optimal development of the charge images. The regulation occurs via a toner marking on the recording medium and its scanning. The toner supply to the developer station is regulated dependent on the scan result.

A further method for testing of the toner portion in the developer
15 mixture with the aid of a toner marking can be learned from WO 00/41038 A.

Experience now shows that both the inking of the latent charge image on the intermediate carrier and the transfer printing of the print image from the intermediate carrier onto the recording medium ~~is~~ are in particular
impaired given printing operation with low toner throughput. Primarily
20 responsible for this quality reduction is a deterioration of the developer that is created by mechanical friction forces given the mixing of carrier and toner. Two-component developer therefore requires a minimum degree of toner throughput in order to prevent the disadvantage cited above, since a too long mixing of the un-refreshed toner with the carrier in the developer station would
25 lead to a damaging of the developer.

Given color printing, the problem of color drift additionally occurs in the case of the too-low print load, and therewith a too-low toner throughput.

SUMMARY

~~The problem to be solved by the invention~~ An object is to specify a
30 method with which a minimum degree of toner throughput is ensured.

~~This problem is ensured according to the features of the claim 1.~~

MARKED COPY

In a method or system to adjust the toner supply to a minimum value in a developer station of an electrographic printing or copying device in which charge images are generated on an intermediate carrier, the charge images being inked with toner at the developer station, a toner concentration is measured in the developer station via a toner marking applied on the intermediate carrier and inked with toner at the developer station. A measurement signal is generated. Dependent on the measurement signal, a supply of the toner to the developer station is regulated. The supply of the toner to the developer station is increased independent of the measured toner concentration upon an under-run of a minimum value of the toner supply per unit time into the developer station so that the transfer of the toner from the developer station to the intermediate carrier is increased.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 illustrates a printing device;

Fig. 2 is an example of the size of a toner marking and, in comparison to this, the size of a control marking; and

Fig. 3 is a flow diagram that shows the steps of the method.

DESCRIPTION OF THE PREFERRED EMBODIMENT

For the purposes of promoting an understanding of the principles of the invention, reference will now be made to the preferred embodiment illustrated in the drawings and specific language will be used to describe the same. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended, such alterations and further modifications in the illustrated device, and/or method, and such further applications of the principles of the invention as illustrated therein being contemplated as would normally occur now or in the future to one skilled in the art to which the invention relates.

The advantage of the inventive method is thus that means that lead to a toner removal from the developer station are always used when the toner supply to the developer station per time unit is too low.

The establishment of the value of the toner supply per time unit can ensue occur in that the number of the conveyances of toner (conveyer cycles)

MARKED COPY

into the developer station per time unit are counted, and the minimum value is fixed at a predetermined number of conveyer cycles per time unit.

~~Developments of the invention result from the dependent claims.~~

The means to increase the toner removal from the developer station
5 can exist in that the transfer of toner to the intermediate carrier is increased, with the result that the toner supply into the developer station is also increased, and ~~therewith~~ thus new toner arrives in the developer station. It is ~~therewith~~ thus prevented that the problem mentioned above occurs. This can be achieved by using a control marking (larger in comparison with the toner
10 marking) on the intermediate carrier and its inking via toner. When it is thus established that too few conveyer cycles are executed, and ~~therewith~~ thus the toner supply is too low, the control marking is thus set until the number of the conveyor cycles is above the predetermined number. The toner marking can subsequently be written again alone on the intermediate carrier, and the
15 printing device can be operated in a typical manner.

The control marking can contain the toner marking or be arranged separate from the toner marking.

~~The invention is explained further using an exemplary embodiment that is shown in Figures.~~

20 ~~Thereby shown are:~~

~~Fig. 1 a printing device;~~

~~Fig. 2 an example of the size of a toner marking and, in comparison to this, the size of a control marking;~~

~~Fig. 3 a flow diagram that shows the steps of the method.~~

25 It is to be learned from Fig. 2 that a control marking ST contains, for example, the toner marking TM_1 but can be selected significantly larger in comparison to the toner marking TM. While the toner marking TM takes up only a small region on the intermediate carrier ZT, the control marking ST can extend over the entire width of the intermediate carrier ZT. The discharge of
30 the intermediate carrier ZT and ~~therewith~~ thus its inking can be selected (shown dashed in Fig. 2) lower than its discharge at the location of the toner marking TM. However, the form of the control marking ST can be freely

MARKED COPY

selected corresponding to the requirements of the respective printing operation. In Fig. 2 the toner marking is integrated into the control marking. The toner marking TM is furthermore necessary for measurement of the toner concentration in the manner specified above.

5 The workflow of the method for adjustment of the toner supply, and ~~therewith~~ thus for toner removal from the developer station, results from Fig. 3.

 In a step S1, it can be checked whether the control marking ST is set (S1 = active). When the control marking ST is set, in step S2 it is tested
10 whether the number n of the conveyor cycles FZ of toner into the developer station (which number n is established via the toner marking regulation) exceeds a predetermined minimum value SW, thus $n(FZ) > SW$. If this is the case, in step S3 exclusively the toner marking TM is set and the normal operation is implemented; otherwise, in step S4 the control marking ST is
15 requested. If, in step S1, it is established that the control marking ST is not active, in step S5 it is checked whether the number n of the conveyor cycles FZ exceeds the predetermined minimum value SW, thus whether $n(FZ) > SW$. If this is the case, in step S6 the toner marking TM alone is requested; otherwise, in step S7 the control marking ST is recalled. The implementation
20 of this method can occur cyclically; for example, in a step S0, every 60 seconds it can be queried whether the control marking ST is set.

 The minimum value of the toner supply per time unit has been established in the exemplary embodiment by the number n of the conveyor cycles FZ/time unit; for example, the minimum value can amount to $SW = 2$
25 conveyor cycles/seconds. However, other means are also possible in order to ensure the toner supply to the developer station.

 Another workflow of the method is likewise possible; it is, however, significant that a method is provided to ensure the toner renewal in the developer station given a too-low toner supply to the developer station.

30 The method can be integrated as software into an already present controller. Such a controller is, for example, known from WO-A-00/41038. The establishment of the conveyor cycles for toner can be integrated into a

MARKED COPY

controller as it is described in WO-A-99/36834, which is herewith included in the disclosure.

Exemplary embodiments of the invention have been described. It is thereby clear that the average man skilled in the art can at any time specify modifications and developments that use the inventive concept. Furthermore, the invention can be realized both by means of electronic components (hardware) and via computer program elements (software or software modules). The invention ~~is thereby~~ may be ~~in particular~~ realized from a combination of electronic hardware elements and software elements~~[[.]],~~ for example. The invention accordingly also ~~includes~~ may include computer program products such as, for example, electronic data media (CD, DVD, diskettes, tape drives), ~~or, respectively,~~ components that are distributed via computer networks (Internet) and/or loaded or stored on computers and in particular into buffers and/or run on computers.

MARKED COPY

Reference list

- ZT—intermediate carrier
- L—charge corotron
- DK—illumination device
- 5 E—developer station
- UDS—transfer printing station
- R—cleaning station
- LSC—erasure corotron
- EDL—discharge lamp
- 10 FX—fixing station
- AT—recording medium
- TM—toner marking
- ST—control marking
- n—number of the conveyer cycles
- 15 FZ—conveyer cycle
- SW—minimum value of the conveyer cycles
- S—steps of the method

MARKED COPY

~~Patent claims~~

WE CLAIM AS OUR INVENTION:

MARKED COPY

ABSTRACT OF THE DISCLOSURE

In a method to adjust the toner supply to a minimum value in a developer station of an electrographic printing or copying device in which charge images are generated on an intermediate carrier, the charge images being inked with toner at the developer station, a toner concentration is measured in the developer station via a toner marking applied on the intermediate carrier and inked with toner at the developer station. A measurement signal is generated. Dependent on the measurement signal, a supply of the toner to the developer station is regulated. The supply of the toner to the developer station is increased independent of the measured toner concentration upon an under-run of a minimum value of the toner supply per unit time into the developer station so that the transfer of the toner from the developer station to the intermediate carrier is increased.